INSTALLATION INSTRUCTION 856 Low Voltage LED Track Luminaires

HHT-856LED, LHT-856LED, JHT-856LED

CAUTION:

Read all instructions before installing. Switch off power before installing or re-lamping. Do not attempt to energize anything other than a track light fixture. All installation shall be in accordance with NEC and all local codes.

OVERVIEW:

Fixtures are designed for use on on WAC "L", "H", "J" series track. They may also be used on other manufacturer's brand of track (consult factory for compatibility).

LAMPING:


- 1. Use 12v MR16 lamp, 50-watt max.
- 2. Look through the open side of the fixture and align the pins of the lamp with the holes in the socket.
- 3. Gently push the front edges of the lamp until you feel it seat in the socket holes.


FIXTURE INSTALLATION

- 1. Note the track has a groove running its length to indicate polarity.
- 2. Note the slant of the locking tab.
- 3. Insert adapter into track slot and rotate adaptor 90° so that the low side of the locking tab faces the grooved side of the track.
- 4. Make sure the locking tab seats in the track slot.
- 5. Removal is the reverse procedure. Track heads may be positioned anywhere along the track length.
- 6. Not suitable for use on wall mounted track.



Responsible Lighting®







Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Ave • Ontario, CA 91761 Phone (800) 526.2588 • Fax (800) 526.2585