ACCENT 120V 5012



LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Landscape accent luminaire. Simple to retrofit existing line voltage systems or coordinate well with a new commercial landscape installation.

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Detachable shroud, 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

	Colo	Color Temp		
5012 Accent 120V	30	3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass


5012-30__

Example: 5012-30BBR

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

SPECIFICATIONS Input: 110V - 120VAC Power: 3.5W to 14.5W Brightness: 100 lm to 900 l

Brightness:	100 lm to 900 lm				
Beam Angle:	15° to 60°				
CRI:	85				
Rated Life:	45,000 hours				



ACCENT 120V 5012

WAC

LANDSCAPE LIGHTING

Accessories

Power Stake	M6000-STAKE	M6000-STAKE			Easy wiring accessory designed for 12V & 120V products Eliminates the need for a separate Junction box
Accent Snoot	5010-SNOOT-BK 5010-SNOOT-BZ 5010-SNOOT-BBR			um num	Shields lamp and reduces glare
6"Long Shroud	5010-LSHR-BK 5010-LSHR-BZ 5010-LSHR-BBR	5010-LSHR-BZ		um num	Reduce glare. Ideal for downlighting application
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK				Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK			num um	Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ "NPT threaded holes
Optics	LENS-20-GRN	Amber Green Red	LENS-20-BLU LENS-20-FR LENS-20-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BK 4 5000-X08-BZ 8 5000-X08-BK 8 5000-X12-BZ 1	4 in 4 in 3 in 3 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760