# **TOUCH PANEL SWITCH WITH OCCUPANCY SENSOR**

WAC LIGHTING

model: CT-6A-R2

Responsible Lighting®

# Controller Fixture Type: Catalog Number: Project: Location:

**Motion Sensor** 

## **Touch Panel**









### **PRODUCT DESCRIPTION**

Intelligent motion and touch switch control of luminaires based on occupancy, compatible with wide range of WAC Lighting low voltage LED lighting luminaires.

### **FEATURES**

Programmed with three functions:

**TOUCH and SENSOR** Touch switch turns the luminaire on/off manually while the motion sensor

turns it off when the space is vacant

**TOUCH** Only touch switch, inactivate motion sensor. **SENSOR** Only motion sensor, inactivate touch switch.

- Built-in adjustable timer on motion sensor allows automatic shut off after the sensor covered area is vacated.
   Maximum time delay is 20 minutes (20MIN), minimum is 10 seconds (10S).
- Motion sensor supplied with 18ft wire and touch panel supplied with 8ft wire. May be cut to desired length.
   Lengthening of wire is not recommended as will decrease sensitivity.
- Two different mounting options (screw or double sided tape mounting) for all undercabinet application included. Choose appropriate mounting option for rough, smooth and curved surfaces.
- Designed for indoor undercabinet application. Recommended ambient temperature is 14° to 122° F (-10° to 50°C)
- 5 year WAC Lighting product warranty

# SPECIFICATIONS

Input/Output Voltage: 12/24V AC/DC.

**Applicable:** WAC Lighting low voltage LED series

Sensor Wire: 24 AWG 18ft length
Touch Wire: 22 AWG 8ft length
Standards: ETL and cETL Listed

Input/Output Current: 6A max

**ORDER NUMBER** 

Model #

CT-6A-R2

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 **Headquarters/Eastern Distribution Center**44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

**Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

# **TOUCH PANEL SWITCH WITH OCCUPANCY SENSOR**


WAC LIGHTING

model: CT-6A-R2

Responsible Lighting®

### **MOTION SENSOR COVERAGE**

Maximum detection angle and distance chart for Motion sensor:



# **Sample Application for TOUCH and SENSOR**

- Designed for indoor undercabinet application. The recommended ambient temperature is 14 to 122 °F (-10 to 50 °C).
- Recommended to use with WAC Lighting Low Voltage LED (12V or 24V) undercabinet products.
- To achieve better result, install motion sensor with lens facing side ways and touch panel within sensor coverage range.

