## PRINCESS - model: DR-362

Crystal Collection: Beauty Spots™

# WAC LIGHTING

## Responsible Lighting®





#### **PRODUCT DESCRIPTION**

Beauty Spots™ series are low voltage surface mount fixtures designed for use in drywall ceilings, grid ceilings, walls, or displays. Clear shades fit over the lamp and are retained by a spring band.

#### **FEATURES**

- · Sold as complete unit housing and trim
- Use 12V/24V remote electronic (order separately)
- · Easily mounted on suspended or finished ceilings
- · Can be used individually as accent pieces or grouped together
- 5 year WAC Lighting product warranty

Fixture Type:
Catalog Number:
Project:
Location:

### **SPECIFICATIONS**

**Construction:** Canopy faceplate is chrome plated, wiring compartment is steel, painted black

Light Source: LED 4.3W or Xenon Bi-Pin 20W

**Mounting:** No screws, nails or hardware required, flat "wing" springs expand against the cut out hole to hold fixture against the surface (2%" cut out hole),

Integral wiring compartment with standard size knock out hole on top. When using a class II power supply, side hole may be used for wire entry

Dimming: ELV Dimming: 100%-10% (Xenon only)

Standards: UL & cUL Listed.

Integral LED * Dimming is not recon	Color Temp	Lumens	Voltage	Wattage	Rated Life	Finish	n Cutout		
2½"   '2¾" ½"	DR-362LED-CL/CH	Princess	3000K	150	24V	4.5 W	50,000 hours	Clear Chroi	73/6"
		Input	Output	Min Load	Dimensi	on (L x W x H)	Max Fixture	Run I	Max Run Length
Remote Transformer for Integral LED	EN-2460-RB2 EN-24100-RB2	120V 120V	24V, 60W (class 2) 24V, 96W (class 2)	1 W 1 W	6½"x 15%"x 1¼" 6½"x 15%"x 1¼"		12 per transformer 21 per transformer		30' 40'

#### 12V Xenon Bi-Pin Rated Life Finish Cutout \* Dimmable with compatible dimmer match to power supply Color Temp Lumens Voltage Wattage 10,000 Clear/ DR-362-CL/CH 3000K 200 20 W Princess 12V, 24V 23/8" hours Chrome Input Output Min Load Dimension (LxWxH) Max Fixture Run Max Run Length EN-1260-RB2 120V 12V, 60W (class 2) 1 W 65/8" x 15/8" x 11/8" 25' Remote Transformer EN-12100-RB-AR 12V, 100W 30' 1W 5 120V 61/4" x 3" x 15/8" for Xenon Bi-pin EN-12150-RB-AR 120V 12V, 150W 1W 6¼" x 3" x 15/8' 35'

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

**Headquarters/Eastern Distribution Center**44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585