
COLOR CRYSTAL – model: DR-G352

Crystal Collection: Beauty Spots™



PRODUCT DESCRIPTION

Beauty Spots[™] series are low voltage surface mount fixtures designed for use in drywall ceilings, grid ceilings, walls, or displays. Clear shades fit over the lamp and are retained by a spring band.

FEATURES

- For use with LED canopy DR-LED302-30-CH or Xenon canopy DR-301 (order separately)
- Use 12V/24V remote electronic or magnetic transformer (order separately) see next pages for complete transformer spec.
- Easily mounted on suspended or finished ceilings.
- · Can be used individually as accent pieces or grouped together.
- 5 year WAC Lighting product warranty

WAC LIGHTING

Responsible Lighting®

Fixture Type:
Catalog Number:
Project:
Location:

SPECIFICATIONS

Construction: Canopy faceplate is plated chrome. Wiring compartment is steel, painted black.

Light Source: LED 4.3W or Xenon Bi-Pin 20W with canopy.

Mounting: No screws, nails or hardware required. Flat "wing" springs expand against the cut out hole to hold fixture against the surface. 2%" cut out hole.


Mounting: Integral wiring compartment with standard size knock out hole on top. When using a class II power suply, side hole may be used for wire entry

Standards: UL & CUL Listed.

Dimming: ELV Dimming, 100%-10%

COMPATIBLE CANOPY

Source	Model #	Finish		Watt	Cutout	Color Temp	Lumens
LED	DR-LED302-30	сн	Chrome	4.3W	2%"	3000K	145
Xenon Bi-Pin	DR-301	СН	Chrome	20W	2%"	2700K	




– CH

Example: DR-LED302-30-CH

ORDER NUMBER

Model #	Color			
DR-G352	AM BL CL	Amber Blue Clear		



Example: DR-G352-AM

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2018

COLOR CRYSTAL – model: DR-G352

Beauty Spots[™] Transformers

WAC LIGHTING

Responsible Lighting®

	Model	Input	Output	Min Load	Dimension (L x W x H)	Max Fixture Run	Max Run Length
Integral LED Canopy	EN-2460-RB2	120V	24V, 60W (class 2)	1W	6½" x 15/8" x 11/4"	12	30'
(Order with DR-LED302-30-CH)	EN-24100-RB2	120V	24V, 96W (class 2)	1W	6½" x 15⁄8" x 1¼"	21	40'
	EN-1260-RB2	120V	12V, 60W (class 2)	1W	6½"x 15/8"x 11/8"	3	25'
Xenon Bi-pin Canopy	EN-1275-RB-AR	120V	12V, 75W	1 W	6½" x 15⁄8" x 1½"	3	30'
(Order with DR-301-CH)	EN-12100-RB-AR	120V	12V, 100W	1 W	6¼" x 3" x 15⁄8"	5	30'
	EN-12150-RB-AR	120V	12V, 150W	1 W	6¼" x 3" x 15⁄8"	7	35'

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 Western Distribution Center 1750 S Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585