

DUORAIL™

Rail System Suspension

WAC LIGHTING

Responsible Lighting®









Fixture Type:

Catalog Number:

Project: _____

Location: _____

Rail Suspension

| | Model # | Finish | Dimensions | Description |
|--|--|---|--------------------------|--|
|  Standard Ceiling Standoff | LM2-X3 LM2-X5 LM2-X8 | BN <i>Brushed Nickel</i> DB <i>Dark Bronze</i> | 3" 5¼" 8" | Supports rail for flat ceilings and surfaces. |
|  T-Bar Ceiling Standoff | LM2-TB3 LM2-TB5 LM2-TB8 | BN <i>Brushed Nickel</i> DB <i>Dark Bronze</i> | 3" 5¼" 8" | Conceals a T-Bar clip under the canopy for standard 1" T-Bar ceilings. |
|  Sloped Ceiling Standoff | LM2-XS5 | BN <i>Brushed Nickel</i> DB <i>Dark Bronze</i> | 5¼" | Supports rail for sloped ceiling. Accommodates angles up to 45°. |
|  Aircraft Suspension Cable | LM2-CS48 LM2-CS96 | BN <i>Brushed Nickel</i> DB <i>Dark Bronze</i> | 48" 96" | Supports monorail for flat or sloped ceilings. |
|  Extension Rod | LM-R12 LM-R24 LM-R36 LM-R48 | BN <i>Brushed Nickel</i> DB <i>Dark Bronze</i> | 12" 24" 36" 48" | Use with standoffs and power feeds. Use two per circuit with rod couplers to extend power feeds. Field cut to size and join with rod couplers. |
|  Rod Coupler | LM-RI | BN <i>Brushed Nickel</i> DB <i>Dark Bronze</i> | Ø¾" × 7/8" H | Use two per power feed, four per dual power feed, one additional coupler per rod needed when joining two rods in excess of 48". |

Example: **LM2-CS48-BN**

WAC Lighting
 www.waclighting.com
 Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive • Port Washington, NY 11050
 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
 1750 Archibald Avenue • Ontario, CA 91760
 Phone (800) 526.2588 • Fax (800) 526.2585