DICE - model: FM-40 dweLED[™] Ceiling Flush Mounts

WAC LIGHTING

Responsible Lighting®

Construction: Durable die-cast aluminum canopy, with thick opal glass.

Dimming: 100%-10% Electronic Low Voltage (ELV)

Standards: ETL & cETL damp location listed, ADA compliant

Fixture Type:
Catalog Number:
Project:
Location:

SPECIFICATIONS

Light Source: LED


PRODUCT DESCRIPTION

Thick-walled glass is uniformly illuminated in a design made for LED technology in a rectangular format. Full range dimming control. Mounts as robust ceiling luminaire or a compelling wall sconce.

FEATURES

- Etched ¾" thick pressed glass diffuser with interior ceramic glaze
- Mount as a ceiling fixture or wall sconce
- ADA compliant when mounted on wall
- ETL & cETL damp location listed
- 100%-10% electronic low voltage (ELV) dimming
- Transformer located in J box
- 277V available (special order)
- CRI: 90
- 45,000 hour rated life
- 5 year warranty

		Color Temp	Watt	LED Lumens	Delivered Lumens	Finish		
<u>14" 25</u> %"	FM-4014-27 FM-4014-30	2700K 3000K	31W 31W	1323 1356	610 640	BN	Brushed Nickel	
<u>6"</u> , 2%"	FM-4006-27 FM-4006-30	2700K 3000K	17.5W 17.5W	779 800	355 365			
<u>9"</u> , 234" []]] []]]9"	FM-4009-27 FM-4009-30	2700K 3000K	27W 27W	1341 1376	885 910	BN BZ CH	Brushed Nickel Bronze Chrome	
<u>12"</u> 25%"	FM-4012-27 FM-4012-30	2700K 3000K	25W 25W	1990 2200	890 985			



Example: FM-4014-27-BN

For 277V, add an "F" before the color temperature: FM-4014F-27-BN

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.