OCULUX – model: 7030

H/L/J Track Luminaire



Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	
Location:	
	7 ¹¹ / ₁₆ " Ø3"

PRODUCT DESCRIPTION

Ideal for retail and higher-mounted residential spaces, the OCULUX 7030 balances the output of a high efficiency LED with the flexibility of three beam spreads and glare control compatibility. Oculux is available in H, J/J2, and L track configurations. Order according to track layout specifications.

FEATURES

• 3 beam angle options included:

- 55° beam film pre-installed, interchangeable 38° film supplied, remove film for 16° spot beam
- Integral driver and high output COB LED
- Outperforms halogen 100W PAR38
- 350° horizontal and 90° vertical aiming
- Accommodates one lens OR one glare control accessory
- 5 year warranty

SPECIFICATIONS

F

Construction:	Die-cast aluminum with baffled front cover for glare control
----------------------	--

Input Power:	32W at 120VAC, 50/60Hz (PF: 0.98)
THD(A):	< 15% Total Harmonic Distortion (Current)
Light Source:	High output 3 Step Mac Adam, Ellipse COB, 90+ CRI Rated Life of 50,000 hours at L70
Dimming:	ELV or Forward Phase: 100 - 10% Reference dimming report for compatibility.
Standards:	ETL & cETL Dry Location Listed, Energy Star® 2.0, Title 24 JA8-2016 Compliant
Finish:	Electrostatically powder coated Black, Dark Bronze, and White Electroplated Brushed Nickel
Operating Temperature:	32°F to 104°F (0°C to 40°C)

1

REPLACEMENT OPTICS

38°	Narrow Flood Film	FILM-20-N
55°	Flood Film	FILM-20-F

System	Model	Beam	Max Lumens	Max CBCP	Color	Гетр	CRI	T24	Energy Star	Finisł	n
 H H Track L L Track J J/J2 Track 	7030	16° 38° 55°	2025 1855 1850	11641 2918 1641	930	3000K	90	Yes	Yes	BK BN DB WT	Black Brushed Nickel Dark Bronze White

-7030-930-

Example: H-7030-930-BN

Accommodates one lens accessory OR one glare control accessory

COLOR L	ENS	FLAT LENS	GLARE CONTROL		
AmberLENS-20-AMBBlueLENS-20-BLUGreenLENS-20-GRNRedLENS-20-RED		Frosted LENS-20- Spread LENS-20- Beam Elongating LENS-20-	SPR Cross Louver - White	LENS-20P-CRL-BK LENS-20P-CRL-BN LENS-20P-CRL-WT LENS-20-SNOOT-BK LENS-20-SNOOT-BN LENS-20-SNOOT-WT LENS-20-HCL	
waclighting.com Phone (800) 526.2588 Fax (800) 526.2585		Headquarters/Eastern D i 44 Harbor Park Drive Port Washington, NY 1105	1600 Distril	tribution Center oution Ct gs, GA 30122	Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760