



HR-2LD-ET109

2" Tesla™ LED High Brightness Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round, High Brightness downlight trim with glass lens

FEATURES

- 2" aperture
- High Brightness Trim
- Damp location listed
- 5° visual cutoff angle for glare control
- 90,000 hours rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)


Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. Damp location listed.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Finish
HR-2LD-ET109 <i>High Brightness Energy Star® Damp Location Listed</i>	S 16.5°	27 2700K	85	665	2921	BN Brushed Nickel CB Copper Bronze WT White
		W 3000K	85	730	3786	
		9W 3000K	90	672	2689	
		35 3500K	85	730	3284	
		C 4000K	85	695	3494	
	N 30°	27 2700K	85	635	1415	
		W 3000K	85	705	1669	
		9W 3000K	90	466	1596	
		35 3500K	85	705	1627	
		C 4000K	85	670	1554	
	F 53°	27 2700K	85	610	788	
		W 3000K	85	695	1089	
		9W 3000K	90	480	880	
		35 3500K	85	690	880	
		C 4000K	85	635	796	



HR-2LD-ET109 - -

Example: HR-2LD-ET109F-9W-BN

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

New Construction

HR-2LED-H09D-ICA <i>IC-Rated, Airtight</i>	120V-277V	HR-2LED-H09D-ICAC <i>IC-Rated, Airtight Chicago Plenum</i>	120V-277V
--	-----------	--	-----------

Remodel

HR-2LED-R09D-A <i>Non-IC, Airtight</i>	120V-277V	HR-2LED-R14D <i>Non-IC</i>	120V-277V
--	-----------	--------------------------------------	-----------

REPLACEMENT MODULES

Reflectors

<i>Spot</i>	SL-REF-LUX10-S
<i>Narrow Flood</i>	SL-REF-LUX10-N
<i>Flood</i>	SL-REF-LUX10-F

LED

2700K	85 CRI	LXS8-PW27
3000K	85 CRI	LXS8-PW30
3000K	90 CRI	LXS9-PW30
3500K	85 CRI	LXS8-PW35
4000K	85 CRI	LXS8-PW40

waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760