
HR-836

2.5" Low Voltage Downlight Trim

WAC LIGHTING

Responsible Lighting®





| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location | |

PRODUCT DESCRIPTION

Smooth round die-cast trim for use with HR-800 series low voltage housings.

FEATURES

- · Retention clips secure lens firmly to lamp
- · 1W minimum load transformers
- · Abrasion resistant powder coat paint or plated metal finish
- · Clear lens included, see opposite page for replaceable lens options
- · Suitable for damp locations.
- · 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Powder coated or plated brushed nickel finish on die-cast aluminum. Inner die-cast aluminum trim body has three retention clips to firmly hold trim to housing. Tension spring holds lens firmly against the lamp.

Light Source: Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

Finish: Brushed Nickel (BN), Copper Bronze (CB), and White (WT) available.

Standards: UL & CUL Listed.

Housings: Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 34" for remodel & 34" for new construction.

Model Finish HR-836 (order lamp separately) HR-836LED (7W 450lm LED MR16 included) Finish BN Brushed Nickel CB Copper Bronze WT White

| HR-836 | _ | |
|--------|---|--|
| | | |

Example: HR-836LED-CB

LED MR16 (ORDER SEPARATELY)

| MR16LED-BAB | ВК |
|---------------|----|
| WIK TOLED-BAB | WT |

LENSES & LOUVERS

| | | AMB | Amber | UV Filter | LENS-16-UVF |
|------------|----------|-----|--------|----------------------|-------------|
| | | BLU | Blue | Frosted Lens | LENS-16-FR |
| Color Lens | LENS-16- | GRN | Green | Spread Lens | LENS-16-SPR |
| | | RED | Red | Beam Elongating Lens | LENS-16-BEL |
| | | YEL | Yellow | Honeycomb Louver | LENS-16-HCL |

| Compatible Housings | | Model | | Installation | Output | Rating | Volt |
|---------------------|-------------|---------|---|-----------------------|---------------------|--------|------|
| | 5" 115%" | HR-801 | Integral Electronic Transformer Advanced auto-reset, soft start and short circuit protection J-box and Transformer Accessible through Ceiling Opening Suitable for Chain Wiring Suitable for Damp Locations | Remodel | 12V, 50W max | Non-IC | 120V |
| R. A. | 59/16" | HR-802 | | New Construction | | | |
| | 23/4" | HR-800* | Thermal Protection in Transformers Only Snap-Out Style Mounting Clips For Cabinet Use Only | Remote Transformer | 12V/24V, 35W max | | |

^{*}Remote Electronic Class 2 Transformer Required (Sold Separately)

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585