
HR-837

2.5" Low Voltage Downlight Trim



PRODUCT DESCRIPTION

Gimbal ring style adjustable trim for use with HR-800 series low voltage miniature housings.

FEATURES

- Retention clips secure lens firmly to lamp
- 1W minimum load transformers
- Abrasion resistant powder coat paint or plated metal finish
- Clear lens included, see opposite page for replaceable lens options
- Suitable for damp locations.
- 5 year WAC Lighting product warranty

ORDER NUMBER

Model	Finis	h
HR-837	BK	Black
(order lamp separately)	BN	Brushed Nickel
HR-837LED	СВ	Copper Bronze
(7W 450lm LED MR16 included)	WT	White

HR-837

Example: HR-837LED-BN

Compatible Housings		Model		Installation	Output	Rating	Volt
	<u>234"</u> 115%" <u>5</u> "	HR-801	 Integral Electronic Transformer Advanced auto-reset, soft start and short circuit protection J-box and Transformer Accessible through Ceiling Opening Suitable for Chain Wiring Suitable for Damp Locations Suitable for parts 	Remodel	12V, 50W max	Non-IC	120V
	5%/6″ 5%/6″ 5″ 13″ 234″	HR-802		New Construction			
	<u>4</u> " <u>2¾"</u>	HR-800*	 Thermal Protection in Transformers Only Snap-Out Style Mounting Clips For Cabinet Use Only 	Remote Transformer	12V/24V, 35W max		

*Remote Electronic Class 2 Transformer Required (Sold Separately)

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC LIGHTING

Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	

Location:

SPECIFICATIONS

Construction: Powder coated or plated brushed nickel finish on die-cast aluminum. Inner die-cast aluminum trim body has three retention clips to firmly hold trim to housing. Tension spring holds lens firmly against the lamp.

Light Source: Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

Finish: Available in Black (BK), Brushed Nickel (BN), Copper Bronze (CB), and White (WT).

Standards: UL & CUL Listed.

Housings: Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 34" for remodel & 34" for new construction.

LED MR16	(ORDER SE	PARATEL	Y)			
MR16LED-E	BAB	BK WT				
LENSES & L	OUVERS					
		AMB	Am	ber	UV Filter	LENS-16-UVF
		BLU	Blu	е	Frosted Lens	LENS-16-FR
Color Lens	LENS-16-	GRN	Gre	en	Spread Lens	LENS-16-SPR
		RED	Rec	1	Beam Elongating Lens	LENS-16-BEL
		YEL	Yell	ow	Honeycomb Louver	LENS-16-HCL