
HR-8411

4" Low Voltage Downlight Trim

WAC LIGHTING

Responsible Lighting®





Fixture Type:	
Catalog Number:	
Catalog Nulliber.	
Duningto	
Project:	
Location:	

PRODUCT DESCRIPTION

Recessed adjustable trim with interior step baffle. For use with HR-8400 series low voltage housings.

FEATURES

- Step baffle, 35° adjustment from vertical recessed downlight
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to ¾" thick
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable stamped metal construction. Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

Finish: Abrasion resistant powder coat painted finish. Available in White baffle with White trim (WT/WT).

Standards: UL & CUL Listed, Suitable for damp locations

ORDER NUMBER

Model #	Finish	Baffle/Trim		
HR-8411 (Order Imap separately)	WT/WT	10/h: in 00/h: in -		
HR-8411LED	WI/WI	White/White		
(7W 450lm LED MR16 included)				

		AMB BLU		LENS-16-UVF LENS-16-FR	UV Filter Frosted Lens	
LENS-16- Color Lens	GRN	Green	LENS-16-SPR	Spread Lens		
		RED	Red	LENS-16-BEL	Beam Elongating Lens	
		YEL	Yellow	LENS-16-HCL	Honeycomb Louver	
		YEL	Yellow	LENS-16-HCL	Honeycomb Louver	

Model # Finish

HR-8411 – WT/WT

Example: HR-8411LED-WT/WT

4" Low Voltage Ho	ousings (Required)		Model	Voltage	Transformer	Output	Installation	Rating
	4½"	5%6"	HR-8402E	120V	Electronic	12V, 50W max	New Construction	Non-IC
	45/16" 13%16"	434"	HR-8401E	120V	Electronic	12V, 50W max	Remodel	Non-IC

ACCESSORIES

Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 34" for remodel & 34" for new construction.