
HR-8412

4" Low Voltage Downlight Trim

WAC LIGHTING

Responsible Lighting®





PRODUCT DESCRIPTION

Recessed adjustable trim with interior reflector. For use with HR-8400 series low voltage housings.

FEATURES

- 35° adjustment from vertical recessed alternative to surface mounted track lights
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

ORDER NUMBER

	Tixtule Type.
13/16"	Catalog Number:
35%" —	Project:
3	Location:

SPECIFICATIONS

Construction: Durable stamped metal construction. Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Utilizes LED or Halogen 12V MR16 lamps (order separately). 50W or 75W maximum, see individual housing for wattage rating.

Finish: Abrasion resistant powder coat painted or plated metal finish. Reflector is available in Clear (CL). Trim is available in Brushed Nickel (BN) or White (WT).

Standards: UL & CUL Listed, Suitable for damp locations

Model #	Finish	Reflector/Trim
HR-8412	BN CL	Clear/Brushed Nickel Clear/White
Model #		Finish

HR-8412 Example: HR-8412-BN



ACCESSORIES

LENS-16-	Color Lens	AMB BLU		LENS-16-UVF LENS-16-FR	UV Filter Frosted Lens Spread Lens	
		GRN		LENS-16-SPR		
		RED	Red	LENS-16-BEL	Beam Elongating Lens	
		YEL	Yellow	LENS-16-HCL	Honeycomb Louver	

Example: HR-8412-B	N								
4" Low Voltage Ho	ousings (Required)		Model	Volta	age	Transformer	Output	Installation	Rating
	4½"	5%6" 0	HR-8402E		120V	Electronic	12V, 50W max	New Construction	Non-IC
	65%6"	61%6"	HR-8402HL*		120V	Magnetic	12V, 75W max	New Construction	Non-IC
N. J. A.	79%6"	10%"	HR-8403	H HF	120V 277V	Magnetic	12V, 50W max	New Construction	IC Airtight
	5½"	611/6"	HR-8402	H HF	120V 277V	Magnetic	12V, 50W max	New Construction	Non-IC
13%e" — 13%e"		HR-8401E		120V	Electronic	12V, 50W max	Remodel	Non-IC	
Res	41/6" 119/6"	\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	HR-8401	H HF	120V 277V	Magnetic	12V, 50W max	Remodel	Non-IC

*Not Compatible with HR-D418 or HR-D418-S Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585