


HR-D324

3" Low Voltage Downlight Trim



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Open baffle trim used to prevent high and low angle aperture glare. For use with HR-300 series low voltage downlight housings. Center lamp holder allows the lamp to be tilted to 25° from nadir.

FEATURES

- Basic baffle, 25° adjustment from vertical
- Die-cast aluminum construction with heavy gauge retention clips secure lens firmly to lamp
- Abrasion resistant powder coat paint or plated metal finish
- Variety of decorative and performance trim options
- Clear lens included
- UL & CUL Listed. Suitable for damp locations.

SPECIFICATIONS

Construction: Powder coated or plated brushed nickel finish on die-cast aluminum. Inner die-cast aluminum trim body has three heavy gauge retention clips to firmly hold trim to housing.

Light Source: Utilizes LED or Halogen 12V MR16 lamps, 50W max. Ordered separately.

Standards: UL & CUL Listed.

Housings: Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

ORDER NUMBER

Model	Finish	Baffle/Trim
HR-D324	WT/WT	White/White

HR-D324 - **WT/WT**

Example: **HR-D324-WT/WT**

LED MR16 (ORDER SEPARATELY)

MR16LED-BAB	BK WT
-------------	----------

LENSES & LOUVERS

Color Lens	LENS-16-	AMB BLU GRN RED YEL	Amber Blue Green Red Yellow	UV Filter Frosted Lens Spread Lens Beam Elongating Lens Honeycomb Louver	LENS-16-UVF LENS-16-FR LENS-16-SPR LENS-16-BEL LENS-16-HCL
------------	----------	---------------------------------	---	--	--

3" Low Voltage Housings (Required)

	Model	Transformer	Installation	Output	Rating	Volt
Non-IC New Construction 	HR-302E HR-302M	<i>Electronic</i> <i>Magnetic</i>	• Integral Electronic or Magnetic Transformer	New Construction		
Non-IC Remodel 	HR-301E	<i>Electronic</i>	• J-Box and Transformer Accessible Through Ceiling • Rated for Branch and Chain Wiring • Suitable for Damp Locations	Remodel	12V, 50W max	Non-IC 120V
Non-IC Remodel 	HR-301M	<i>Magnetic</i>	• Suitable for use in "Shallow" Joist Installations	Remodel		

Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585