


HR-D327

3" Low Voltage Downlight Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Adjustable open gimbal ring trim for use with HR-300 series low voltage downlight housings.

FEATURES

- Adjustable gimbal ring, 25° adjustment from vertical
- Die-cast aluminum construction with heavy gauge retention clips secure lens firmly to lamp
- Abrasion resistant powder coat paint or plated metal finish
- Variety of decorative and performance trim options
- Clear lens included
- UL & CUL Listed. Suitable for damp locations.

SPECIFICATIONS

Construction: Powder coated finish on die-cast aluminum. Inner die-cast aluminum trim body has three heavy gauge retention clips to firmly hold trim to housing.

Light Source: Utilizes LED or Halogen 12V MR16 lamps, 50W max. Ordered separately.

Standards: UL & CUL Listed.

Housings: Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

ORDER NUMBER

Model	Finish	
HR-D327	BN	Brushed Nickel
	WT	White

HR-D327 -

Example: **HR-D327-BN**

LED MR16 (ORDER SEPARATELY)

MR16LED-BAB	BK
	WT

LENSES & LOUVERS

Color Lens	LENS-16-AMB	Amber	UV Filter	LENS-16-UVF
	LENS-16-BLU	Blue	Frosted Lens	LENS-16-FR
	LENS-16-GRN	Green	Spread Lens	LENS-16-SPR
	LENS-16-RED	Red	Beam Elongating Lens	LENS-16-BEL
	LENS-16-YEL	Yellow	Honeycomb Louver	LENS-16-HCL

3" Low Voltage Housings (Required)

	Model	Transformer	Installation	Output	Rating	Volt
<p><i>Non-IC New Construction</i></p> <p>HR-302E <i>Electronic</i> HR-302M <i>Magnetic</i></p>		<ul style="list-style-type: none"> • Integral Electronic or Magnetic Transformer 	New Construction			
<p><i>Non-IC Remodel</i></p> <p>HR-301E <i>Electronic</i></p>		<ul style="list-style-type: none"> • J-Box and Transformer Accessible Through Ceiling • Rated for Branch and Chain Wiring • Suitable for Damp Locations 	Remodel	12V, 50W max	Non-IC	120V
<p><i>Non-IC Remodel</i></p> <p>HR-301M <i>Magnetic</i></p>		<ul style="list-style-type: none"> • Suitable for use in "Shallow" Joist Installations 	Remodel			

Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585