
### HR-D412-S

## 4" Low Voltage Downlight Trim

# **WAC LIGHTING**

## Responsible Lighting®





Fixture Type:	
Catalog Number:	
Project:	
Location:	

#### **PRODUCT DESCRIPTION**

Square recessed adjustable trim with interior reflector. For use with HR-8400 series low voltage housings.

#### **FEATURES**

- Square open reflector for optimized performance without more power
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

**Construction:** Die-cast aluminum construction Three heavy gauge retention clips firmly hold trim to housing.

**Lamp:** Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

**Finish:** Trim available in electroplated Brushed Nickel (BN) and powder coat White (WT). Reflector is Specular Clear (SC).

Standards: UL & CUL Listed, Suitable for damp locations

#### **ORDER NUMBER**

Model #	Finish	Reflector/Trim
HR-D412-S (order lamp separately)	SC/BN	Clear/Brushed Nickel
HR-D412LED-S	SC/WT	Clear/White
(7W 450lm LED MD16 included)		

<b>HR-D412LED-S</b> (7W 450lm LED MD16 included)		SC/WT	Clear/White
Model #	Finish		
HR-D412 -S -			

#### **ACCESSORIES**

		AMB BLU		LENS-16-UVF LENS-16-FR	UV Filter Frosted Lens		
LENS-16- Color Lens		GRN	Green	LENS-16-SPR	Spread Lens		
		RED	Red	LENS-16-BEL	Beam Elongating Lens		
		YEL	Yellow	LENS-16-HCL	Honeycomb Louver		

Example: HR-D412LED-S-SC/BN

4" Low Voltage Ho	ousings (Required)		Model	Voltage	Transformer	Output	Installation	Rating
	4/4" ———————————————————————————————————	5%6"	HR-8402E	120V	Electronic	12V, 50W max	New Construction	Non-IC
	49/6" 139/6"	4½" 4½" ——	HR-8401E	120V	Electronic	12V, 50W max	Remodel	Non-IC

Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 3" for remodel & 3" for new construction.