
## HR-D412

### 4" Low Voltage Downlight Trim





#### **PRODUCT DESCRIPTION**

Recessed adjustable trim with interior reflector. For use with HR-8400 series low voltage housings.

#### FEATURES

- 35° adjustment from vertical recessed alternative to surface mounted track lights
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to <sup>3</sup>/<sub>4</sub>" thick
- 5 year WAC Lighting product warranty

# WAC LIGHTING

#### Responsible Lighting®

Fixture Type:	
Catalog Number	:
Project:	
Location:	

#### SPECIFICATIONS

AMB

BLU

GRN

RED

YEL

Amber

Blue

Red

Green

Yellow

**Construction:** Durable die-cast aluminum trim with specular anodized aluminum reflector. Three heavy gauge retention clips firmly hold trim to housing.

**Lamp:** Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

**Finish:** Trim available in electroplated Brushed Nickel (BN) and powder coat White (WT). Reflector is Specular Clear (SC).

LENS-16-UVF

LENS-16-FR

LENS-16-SPR

LENS-16-BEL

LENS-16-HCL

**UV** Filter

**Frosted Lens** 

Spread Lens

Beam Elongating Lens

Honeycomb Louver

Standards: UL & CUL Listed, Suitable for damp locations

#### ORDER NUMBER

# Model #FinishReflector/TrimHR-D412<br/>(Order lamp separately)SC/BNClear/Brushed NickelHR-D412LED<br/>(7W 450lm LED MR16 included)SC/WTClear/White

Finish

Model #

HR-D412 –

#### Example: HR-D412LED-SC/WT

4" Low Voltage H	lousings (Required)	Model	Voltage	Transformer	Output	Installation	Rating
B. A	4 <sup>4</sup> / <sub>1</sub> "	HR-8402E	120V	Electronic	12V, 50W max	New Construction	Non-IC
	45%e <sup>rr</sup> 13%e <sup>rr</sup>	 HR-8401E	120V	Electronic	12V, 50W max	Remodel	Non-IC

Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

#### ACCESSORIES

LENS-16- Color Lens