
## HR-D413

# 4" Low Voltage Downlight Trim

# **WAC LIGHTING**

### Responsible Lighting®





Fixture Type:	
Catalog Number:	
Project:	

#### **PRODUCT DESCRIPTION**

Slotted aperture trim with black interior. Used for controlled highlighting or drama from a small aperture. For use with HR-8400 series low voltage housings.

#### **FEATURES**

- · Slot trim, 35° adjustment from vertical recessed downlight
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

Location:

**Construction:** Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

**Lamp:** Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

**Finish:** Abrasion resistant powder coat painted finish. Available in White (WT).

Standards: UL & CUL Listed, Suitable for damp locations

#### **ORDER NUMBER**

Model #	Finish
HR-D413 (Order lamps separately)	
HR-D413LED	<b>WT</b> White
(7W 450lm LED MR16 included)	

Model # Finish - WT

**ACCESSORIES** 

LENS-16- Color Lens	AMB BLU GRN RED	Blue Green	LENS-16-UVF LENS-16-FR LENS-16-SPR LENS-16-BEL	UV Filter Frosted Lens Spread Lens Beam Elongating Lens
	YEL	Yellow	LENS-16-BEL	Honeycomb Louver

Example: HR-D413LED-WT

4" Low Vo	ltage Ho	usings (Required)		Model	Voltage	Transformer	Output	Installation	Rating
PA S		4/4"	5%6"   811/16"	HR-8402E	120V	Electronic	12V, 50W max	New Construction	Non-IC
		45%6" 139%6" -	4/4"	HR-8401E	120V	Electronic	12V, 50W max	Remodel	Non-IC

Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to %" for remodel & %" for new construction.