# HR-D416

# 4" Low Voltage Downlight Trim



### PRODUCT DESCRIPTION

Periscope style recessed adjustable trim. For use with HR-8400 series low voltage housings.

#### FEATURES

- Directional spot, 30° adjustment from vertical recessed downlight
- Center lamp holder allows lamp to be tilted up to 30° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

# WAC LIGHTING

# Responsible Lighting®

Fixture Type:
Catalog Number:
Project:
Location:

#### SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

Finish: Abrasion resistant powder coat painted or plated metal finish. Available in Brushed Nickel (BN), and White (WT).

Standards: UL & CUL Listed, Suitable for damp locations

## ORDER NUMBER

# Model #FinishHR-D416<br/>(Order lamp separately)BN<br/>HR-D416LED<br/>(7W 450Im LED MR16 included)Brushed Nickel<br/>WhiteModel #FinishHR-D416-

ACCESSORIES											
	AMB	Amber	LENS-16-UVF	UV Filter							
	BLU	Blue	LENS-16-FR	Frosted Lens							
LENS-16- Color Lens	GRN	Green	LENS-16-SPR	Spread Lens							
	RED	Red	LENS-16-BEL	<b>Beam Elongating Lens</b>							
	YEL	Yellow	LENS-16-HCL	Honeycomb Louver							

## Example: HR-D416LED-WT

4″ Low Vol	tage Ho	usings (Required)		Model	Voltage	Transformer	Output	Installation	Rating
B	TA	4 <sup>1</sup> / <sub>4</sub> <sup></sup>		HR-8402E	120V	Electronic	12V, 50W max	New Construction	Non-IC
		45%6″ 139%8″ -	4 <sup>"</sup>	HR-8401E	120V	Electronic	12V, 50W max	Remodel	Non-IC

Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050