
HR-LED418-NIC-RO – Invisible Trim[™]

4" LEDme® – IC-Rated, New Construction Housing



PRODUCT DESCRIPTION

4 inch LEDme[®] Invisible Trim[™] IC-Rated new construction housing, includes six 3W LED's. Includes spackle ring to permit a stable finished installation with a drywall ceiling. For use with LEDme[®] 4 inch round Invisible Trims[™].

FEATURES

Enery Star[®]

- Cutout: 43/8"
- Trims recess into housings flush to the ceiling
- 100,000 hour rated life
- Accommodates ceiling thickness up to 1"
- UL and CUL Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Model #	Color Temp	Watt	Lumens	Efficacy	CRI
HR-LED418-NIC-RO-27	2700K	10.2W	639	58.1 Lm/W	85
HR-LED418-NIC-RO-30	3000K	10.2W	639	58.1 Lm/W	85
HR-LED418-NIC-RO-35	3500K	10.2W	681	62.0 Lm/W	80
HR-LED418-NIC-RO-40	4000K	10.2W	815	70.0 Lm/W	75

ORDER NUMBER

Model #	Color Temp	
HR-LED418-NIC-RO	27 2700K	
	30	3000K
	35	3500K
	40	4000K

HR-LED418-NIC-RO

Example: HR-LED418-NIC-ROC

COMPATIBLE TRIMS

REPLACEMENT MODULES

Model #	Color Temp
RM-6X3-27	2700K
RM-6X3-30	3000K
RM-6X3-35	3500K
RM-6X3-40	4000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

WAC LIGHTING

Responsible Lighting[®]

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Housing and junction box are 20 gauge steel. Frame, hanger bars and spackle trim are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120VAC/60Hz input, 10.2W output, 450mA current. Power factor >0.9. Dimming with thermal protection.

Light Source: Includes six 3W ANSI compliant Warm/Neutral LEDs for the finest color consistency possible. Replacement modules available.

Dimming: May be dimmed to 1% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from $14\frac{1}{2}$ "- $24\frac{1}{2}$ " to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 43%" cutout hole. See instruction sheet for details on installation using spackle ring.

Rating: IC-Rated: Suitable for direct contact with insulation.

Standards: UL & CUL Listed.

Model #	Description	Finish – (where there is a slash (/) the letters correspond as: interior finish/exterior finish)
HR-LED411TL	Round, Open Reflector Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
HR-LED421TL	Round, Step Baffle Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
Example: HR-LED411TL-BK/BN		See individual trim spec sheets for complete information.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585


WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2017


HR-LED418-NIC-RO – Invisible Trim™


Photometrics


WAC LIGHTING

Responsible Lighting®









AVERAGE BEAM ANGLE (50%) : 31.4 DEG


WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

4500K

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

HR-LED418-N-RO – Invisible Trim[™]

4" LEDme® – Non-IC, New Construction Housing



PRODUCT DESCRIPTION

4 inch LEDme[®] Invisible Trim[™] Non-IC new construction housing, includes six 3W LED's. Includes spackle ring to permit a stable finished installation with a drywall ceiling. For use with LEDme[®] 4 inch round Invisible Trims[™].

FEATURES

Enery Star[®]

- Cutout: 43/8"
- Trims recess into housings flush to the ceiling
- 100,000 hour rated life
- Accommodates ceiling thickness up to 1"
- UL and CUL Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Model #	Color Temp	Watt	Lumens	Efficacy	CRI
HR-LED418-N-RO-27	2700K	16W	846	56.4 Lm/W	85
HR-LED418-N-RO-30	3000K	16W	846	56.4 Lm/W	85
HR-LED418-N-RO-35	3500K	16W	901	60.1 Lm/W	80
HR-LED418-N-RO-40	4000K	16W	1135	67.1 Lm/W	75

ORDER NUMBER

Model #	Color Temp		
HR-LED418-N-RO	27 2700K		
		3000K	
	35	3500K	
	40	4000K	

HR-LED418-N-RO

Example: HR-LED418-N-ROC

COMPATIBLE TRIMS

REPLACEMENT MODULES		
Model #	Color Ter	

Model #	Color lemp
RM6X3-27-DL	2700K
RM6X3-30-DL	3000K
RM6X3-35-DL	3500K
RM6X3-40-DL	4000K

Fixture Type:
Catalog Number:
Project:
Location:

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Housing and junction box are 20 gauge steel. Frame, hanger bars and spackle trim are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120VAC/60Hz input, 16W output, 700mA current. Power factor >0.9. Dimming with thermal protection.

Light Source: Includes six 3W ANSI compliant Warm/Neutral LEDs for the finest color consistency possible. Replacement modules available.

Dimming: May be dimmed to 1% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from $14\frac{1}{2}$ "- $24\frac{1}{2}$ " to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 4%" cutout hole. See instruction sheet for details on installation using spackle ring.

Rating: Non-IC: insulation must be kept at least 3" away from the housing.

Standards: UL & CUL Listed.

Model #	Description	Finish – (where there is a slash (/) the letters correspond as: interior finish/exterior finish)		
HR-LED411TL	Round, Open Reflector Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)		
HR-LED421TL	Round, Step Baffle Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)		
Example: HR-LED411TL-BK/BN		See individual trim spec sheets for complete information.		

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2017

WAC LIGHTING


Responsible Lighting[®]

HR-LED418-N-RO – Invisible Trim™


Photometrics


WAC LIGHTING

Responsible Lighting®



4500K





AVERAGE BEAM ANGLE (50%) : 31.4 DEG

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

HR-LED418-N-RO-XX-EM – Invisible Trim™

4" LEDme® – Non-IC, New Construction Housing **Emergency Backup Battery**



WAC LIGHTING

Responsible Lighting®

Catalog Number		
Catalog Number:		
Project:		
Location:		

PRODUCT DESCRIPTION

4 inch LEDme[®] Invisible Trim[™] Non-IC new construction housing, includes six 3W LED's. Includes spackle ring to permit a stable finished installation with a drywall ceiling. For use with LEDme® 4 inch round Invisible Trims™.

FEATURES

- Enery Star®
- Cutout: 43/8"
- 90 min emergency backup battery
- Trims recess into housings flush to the ceiling
- 100,000 hour rated life
- Accommodates ceiling thickness up to 1"
- UL and CUL Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Model #	Color Temp	Watt	Lumens	Efficacy	CRI
HR-LED418-N-RO-27	2700K	16W	846	56.4 Lm/W	85
HR-LED418-N-RO-30	3000K	16W	846	56.4 Lm/W	85
HR-LED418-N-RO-35	3500K	16W	901	60.1 Lm/W	80
HR-LED418-N-RO-40	4000K	16W	1135	67.1 Lm/W	75

ORDER NUMBER

Model #	Color Temp		EM Battery
HR-LED418-N-RO	27	2700K	EM
	30	3000K	
	35	3500K	
	40	4000K	



Example: HR-LED418-N-ROC-EM

COMPATIBLE TRIMS

Model #	Description	Finish – (where there is a slash (/) the letters correspond as: interior finish/exterior finish)
HR-LED411TL	Round, Open Reflector Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
HR-LED421TL	Round, Step Baffle Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
Example: HR-LED411TL-BK/BN		See individual trim spec sheets for complete information.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Housing and junction box are 20 gauge steel. Frame, hanger bars and spackle trim are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120VAC/60Hz input, 16W output, 700mA current. Power factor >0.9. Dimming with thermal protection. 90 min emergency backup battery.

Light Source: Includes six 3W ANSI compliant Warm/Neutral LEDs for the finest color consistency possible. Replacement modules available.

Dimming: May be dimmed to 1% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from $14\frac{1}{2}$ "-24 $\frac{1}{2}$ " to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 43%" cutout hole. See instruction sheet for details on installation using spackle ring.

Rating: Non-IC: insulation must be kept at least 3" away from the housing.

Standards: UL & CUL Listed.

REPLACEMENT MODULES


Model #	Color Temp
RM6X3-27-DL	2700K
RM6X3-30-DL	3000K
RM6X3-35-DL	3500K
RM6X3-40-DL	4000K


HR-LED418-N-RO-XX-EM

Invisible Trim[™] – Photometrics

WAC LIGHTING

Responsible Lighting®







3000K

4500K







AVERAGE BEAM ANGLE (50%) : 31.4 DEG

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2017