
HR-LED421TL - Invisible Trim™

4" LEDme® Step Baffle Downlight Trim







Fixture Type:	
_	
Catalog Number:	
_	
Project:	
Location:	
Location.	

PRODUCT DESCRIPTION

Round recessed trim with interior step baffle.

Designed to sit flush with the ceiling for a clean, architectural look.

For use with HR-LED418 Invisible Trim™ series housings.

FEATURES

- · Flush mount, no profile die-cast aluminum trim
- Recessed depth from LEDs to trim edge is 2%"
- · Narrow flood beam spread
- Deep regression produces a very low glare with 40° cut-off angle
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

Light Source: Utilizes six 3W LED's (included with housing). See individual housing for wattage rating.

Finish: Powder coat paint or plated metal finish. Available in Black baffle w/Brushed Nickel trim (BK/BN), Black baffle w/White trim (BK/WT) and White baffle w/White trim (WT/WT).

Standards: UL & CUL Listed.

ORDER NUMBER

Model #	Finish	Baffle/Trim
HR-LED421TL	BK/BN	Black/Brushed Nickel
	BK/WT	Black/White
	WT/WT	White/White

F	II	۱I	S	Н	E	S







HR-LED421TL -

Example: HR-LED421TL-WT/WT

COMPATIBLE HOUSINGS

Rating	Model #	Installation	Colo	or Temp		Watt	Lumens	CRI	Input	Current	Dimensions			Cutout
IC-Rated	HR-LED418-NIC-RO	New Contruction	27 W	2700K 3000K	11	1114/	639 639	85 85	120V 50/60Hz	450mA	L: 15-24½"	W: 6¾"	H: 5½"	43/8"
	HR-LED418-RIC-RO	Remodel	35 C	35 3500K C 4500K		1100	681 768	80 75			L: 11%"	W: 63/8"	H: 55/8"	43/8"
Non-IC	HR-LED418-N-RO	New Contruction	27 W	2700K 3000K	15	1514/	846 846	85 85	120V	700mA	L: 15-24½"	W: 6¾"	H: 5½"	43⁄8"
	HR-LED418-R-RO	Remodel	35 C	3500K 4500K		15W	901 1003	80 75	50/60Hz		L: 11%"	W: 6 ³ / ₈ "	H: 55/8"	43/8"
Non-IC	HR-LED418-N-RO	New Contruction Emergency Backup Battery	27 W 35 C	2700K 3000K 3500K 4500K	EM	15W	846 846 901 1003	85 85 80 75	120V 50/60Hz	700mA	L: 15-24½"	W: 111/8"	H: 5½"	43⁄8"

Example: HR-LED418-NIC-RO27 or HR-LED418-NIC-RO27-EM

See individual housing spec sheets for complete information.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 **Headquarters/Eastern Distribution Center**44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585