


# HR-LED471

## 4" LEDme® Lensed Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Square recessed lensed trim with interior woven lens.  
For use with HR-LED418 series housings.

### FEATURES

- Less than 1/8" thick, super low profile die-cast aluminum trim
- Recessed depth from LEDs to trim edge is 2 3/4"
- Narrow flood beam spread
- Deep regression produces a very low glare with 40° cut-off angle
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction.  
Three heavy gauge retention clips firmly hold trim to housing.

**Light Source:** Utilizes six 3W LED's (included with housing).  
See individual housing for wattage rating.

**Finish:** Powder coat paint or plated metal finish.  
Available in Chrome (CH) and White (WT).

**Standards:** UL Listed for damp locations.

### ORDER NUMBER

Model #	Finish	Trim
<b>HR-LED471</b>	<b>CH</b>	Chrome
	<b>WT</b>	White

### FINISHES


CH



WT



### PHOTOMETRY



Beam Angle: 31.4°

**HR-LED471** –

Example: **HR-LED471-CH**

### COMPATIBLE HOUSINGS (ORDER SEPARATELY)

Rating	Model #	Installation	Color Temp	Watt	Lumens	CRI	Input	Current	Dimensions	Cutout
IC-Rated	<b>HR-LED418-NIC</b>	<i>New Construction</i>	<b>27</b> 2700K	10.2W	639	85	120V 50/60Hz	450mA	L: 14½-24½" W: 6¾" H: 5½"	4¾"
			<b>30</b> 3000K		639	85				
	<b>HR-LED418-RIC</b>	<i>Remodel</i>	<b>35</b> 3500K		681	80				
Non-IC	<b>HR-LED418-N</b>	<i>New Construction</i>	<b>27</b> 2700K	16W	846	85	120V 50/60Hz	700mA	L: 14½-24½" W: 6¾" H: 5½"	4¾"
			<b>30</b> 3000K		846	85				
	<b>HR-LED418-R</b>	<i>Remodel</i>	<b>35</b> 3500K		901	80				
			<b>40</b> 4000K		1135	75				
Non-IC	<b>HR-LED418-N</b>	<i>New Construction Emergency Backup Battery</i>	<b>27</b> 2700K	<b>EM</b> 16W	846	85	120V 50/60Hz	700mA	L: 14½-24½" W: 11½" H: 5½"	4¾"
<b>30</b> 3000K	846	85								
<b>35</b> 3500K	901	80								
<b>40</b> 4000K	1135	75								

Example: **HR-LED418-NIC-27** or **HR-LED418-NIC-27-EM**

See individual housing spec sheets for complete information.

### WAC Lighting

www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

### Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

### Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760  
Phone (800) 526.2588 • Fax (800) 526.2585