


# HR2LD-ET109P

## 2" Tesla™ Pro LED High Brightness Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Minimum profile, round, High Brightness downlight trim with glass lens

### FEATURES

- 2" aperture
- High Brightness Trim
- Wet location listed
- 5° visual cutoff angle for glare control
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Light Source:** Utilizes one 14.5W LED, CRI: 85 & 90+

**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)

**Mounting:** Two heavy gauge retention clips hold trim firmly to housing

**Finish:** White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

**Standards:** ETL & cETL Listed. Fixtures with \* are Title 24 JA8-2016 Compliant.

### TRIMS

Model#	Beam	Color Temp		CRI	Lumens	CBCP	Finish
HR2LD-ET109P <i>High Brightness Wet Location Listed</i>	N 30°	<b>827</b>	2700K	85	955	1765	BN <i>Brushed Nickel</i> CB <i>Copper Bronze</i> WT <i>White</i>
		<b>927*</b>	2700K	90	775	1436	
		<b>830</b>	3000K	85	990	1807	
		<b>930*</b>	3000K	90	880	1619	
		<b>835</b>	3500K	85	1080	2015	
		<b>840</b>	4000K	85	1090	2035	
	F 55°	<b>827</b>	2700K	85	935	972	
		<b>927*</b>	2700K	90	760	777	
		<b>830</b>	3000K	85	975	995	
		<b>930*</b>	3000K	90	860	878	
		<b>835</b>	3500K	85	1055	1090	
		<b>840</b>	4000K	85	1075	1106	

**HR2LD-ET109P**

Example: HR2LD-ET109PF835CB

**COMPATIBLE HOUSINGS** See individual housing spec sheets for complete information.

### REPLACEMENT MODULES

#### New Construction

<b>HR-2LED-H09D-ICA</b> <i>IC-Rated, Airtight</i>	120V-277V	<b>HR-2LED-H09D-ICAC</b> <i>IC-Rated, Airtight Chicago Plenum</i>	120V-277V
--	-----------	--	-----------

#### Reflectors

<i>Narrow Flood</i>	<b>SL-REF-BL10-1-N</b>
<i>Flood</i>	<b>SL-REF-BL10-1-F</b>

#### Remodel

<b>HR-2LED-R09D-A</b> <i>Non-IC, Airtight</i>	120V-277V	<b>HR-2LED-R14D</b> <i>Non-IC</i>	120V-277V
--	-----------	--------------------------------------	-----------

#### LED

2700K (90 CRI)	<b>BXRC-27G1000-B-23</b>
2700K	<b>BXRC-27E1000-B-23</b>
3000K (90 CRI)	<b>BXRC-30G1000-B-23</b>
3000K	<b>BXRC-30E1000-B-23</b>
3500K	<b>BXRC-35E1000-B-23</b>
4000K	<b>BXRC-40E1000-B-23</b>

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760