


# HR2LEDT509P

2" Tesla™ Pro LED Square 0-30° Adjustable

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Minimum profile, square 0° to 30° adjustable trim with interior open reflector.

## FEATURES

- 2" aperture
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

## SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Light Source:** Utilizes one 14.5W LED, CRI: 85 & 90+

**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)

**Mounting:** Two heavy gauge retention clips hold trim firmly to housing

**Finish:** White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

**Standards:** ETL & cETL Listed. Fixtures with \* are Title 24 JA8-2016 Compliant.

## TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Finish
HR2LEDT509P 0°-30° Adjustable	N 30°	827 2700K	85	795	1870	BN Brushed Nickel CB Copper Bronze WT White
		927* 2700K	90	645	1504	
		830 3000K	85	820	1895	
		930* 3000K	90	740	1801	
		835 3500K	85	895	2075	
		840 4000K	85	910	2164	
	F 45°	827 2700K	85	765	1066	
		927* 2700K	90	620	876	
		830 3000K	85	800	1099	
		930* 3000K	90	705	988	
		835 3500K	85	860	1205	
		840 4000K	85	870	1226	

## HR2LEDT509P

Example: HR2LEDT509PF835BN

**COMPATIBLE HOUSINGS** See individual housing spec sheets for complete information.

### New Construction

<b>HR-2LED-H09D-ICA</b> IC-Rated, Airtight 120V-277V	<b>HR-2LED-H09D-ICAC</b> IC-Rated, Airtight Chicago Plenum 120V-277V
--	---

### Remodel

<b>HR-2LED-R14D</b> Non-IC 120V-277V
--

## REPLACEMENT MODULES

### Reflectors

Narrow Flood	<b>SL-REF-BL10-1-N</b>
Flood	<b>SL-REF-BL10-1-F</b>

### LED

2700K (90 CRI)	<b>BXRC-27G1000-B-23</b>
2700K	<b>BXRC-27E1000-B-23</b>
3000K (90 CRI)	<b>BXRC-30G1000-B-23</b>
3000K	<b>BXRC-30E1000-B-23</b>
3500K	<b>BXRC-35E1000-B-23</b>
4000K	<b>BXRC-40E1000-B-23</b>

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760