


HR2LEDT709P

2" Tesla™ Pro LED Open Reflector Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, square downlight trim with interior open reflector

FEATURES

- 2" aperture
- Damp location listed
- 30° visual cutoff angle for glare control
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. Fixtures with * are Title 24 JA8-2016 Compliant.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Finish
HR2LEDT709P <i>Open Reflector</i>	N 30°	827 2700K	85	810	1844	BN Brushed Nickel CB Copper Bronze WT White
		927* 2700K	90	660	1510	
		830 3000K	85	845	1919	
		930* 3000K	90	755	1721	
		835 3500K	85	910	2079	
		840 4000K	85	935	2163	
	F 45°	827 2700K	85	1073	1073	
		927* 2700K	90	848	848	
		830 3000K	85	1089	1089	
		930* 3000K	90	990	990	
		835 3500K	85	1189	1189	
		840 4000K	85	1213	1213	

HR2LEDT709P

Example: HR2LEDT709PF835WT

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

REPLACEMENT MODULES

New Construction

HR-2LED-H09D-ICA <i>IC-Rated, Airtight</i>	120V-277V	HR-2LED-H09D-ICAC <i>IC-Rated, Airtight Chicago Plenum</i>	120V-277V
--	-----------	--	-----------

Reflectors

Narrow Flood	SL-REF-BL10-1-N
Flood	SL-REF-BL10-1-F

Remodel

HR-2LED-R09D-A <i>Non-IC, Airtight</i>	120V-277V	HR-2LED-R14D <i>Non-IC</i>	120V-277V
--	-----------	--------------------------------------	-----------

LED

2700K (90 CRI)	BXRC-27G1000-B-23
2700K	BXRC-27E1000-B-23
3000K (90 CRI)	BXRC-30G1000-B-23
3000K	BXRC-30E1000-B-23
3500K	BXRC-35E1000-B-23
4000K	BXRC-40E1000-B-23

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760