


HR3LEDT218P

3.5" Tesla™ Pro LED Shower Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round shower trim with interior open reflector.

FEATURES

- 3.5" aperture
- Wet location listed
- 30° visual cutoff angle for glare control
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Power Consumption: 21.5W

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing.

Finish: Powder coated white
Electroplated brushed nickel and copper bronze

Standards: ETL & cETL Listed. Fixtures with * are Title 24 JA8-2016 Compliant.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Finish
HR3LEDT218PN <i>Shower Light</i> <i>Wet Location Listed</i>	30°	827 2700K	85	1100	2274	BN <i>Brushed Nickel</i> CB <i>Copper Bronze</i> WT <i>White</i>
		927* 2700K	90	920	1896	
		830 3000K	85	1135	2316	
		930* 3000K	90	1040	2153	
		835 3500K	85	1240	2569	
840 4000K	85	1256	2547			

HR3LEDT218PN

Example: HR3LEDT218PN927BN

COMPATIBLE HOUSINGS *See individual housing spec sheets for complete information.*

New Construction

HR-3LED-H18D1-ICA <i>Narrow, IC-Rated, Airtight</i>	120V-277V	HR-3LED-H18D1-ICAC <i>Narrow, IC-Rated, Airtight Chicago Plenum</i>	120V-277V
HR-3LED-H18D-ICA <i>IC-Rated, Airtight</i>	120V-277V	HR-3LED-H18D-ICAC <i>IC-Rated, Airtight Chicago Plenum</i>	120V-277V
HR-3LED-H18D-EMICA <i>IC-Rated, Airtight Emergency Backup Battery</i>	120V	HR3LED-H18D-EMICAF <i>IC-Rated, Airtight Emergency Backup Battery</i>	277V
HR-3LED-H18D-A <i>New Construction Non-IC, Airtight</i>	120V-277V		

Remodel

HR-3LED-R18D-A <i>Non-IC, Airtight</i>	120V-277V	HR-3LED-R22D <i>Non-IC</i>	120V-277V
--	-----------	--------------------------------------	-----------

REPLACEMENT MODULES

Reflectors

<i>Narrow Flood Flood</i>	SL-REF-BL10-1-N SL-REF-BL10-1-F
---------------------------	--

LED

2700K	85 CRI	BXRC-27E1000-B-03
2700K	90 CRI	BXRC-27G1000-B-03
3000K	85 CRI	BXRC-30E1000-B-03
3000K	90 CRI	BXRC-30G1000-B-03
3500K	85 CRI	BXRC-35E1000-B-03
4000K	85 CRI	BXRC-40E1000-B-03

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760