


# HR3LEDT718P

## 3.5" Tesla™ Pro LED Open Reflector

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Minimum profile, square downlight trim with interior open reflector

### FEATURES

- 3.5" aperture
- Damp location listed
- 30° visual cutoff angle for glare control
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Power Consumption:** 21.5W

**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)


**Mounting:** Two heavy gauge retention clips hold trim firmly to housing.

**Finish:** Powder coated white  
Electroplated brushed nickel and copper bronze

**Standards:** ETL & cETL Listed. Fixtures with \* are Title 24 JA8-2016 Compliant.

### TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Finish
HR3LEDT718P Open Reflector	N 30°	<b>827</b> 2700K	85	1190	2570	<b>BN</b> Brushed Nickel <b>CB</b> Copper Bronze <b>WT</b> White
		<b>927*</b> 2700K	90	1005	2183	
		<b>830</b> 3000K	85	1235	2650	
		<b>930*</b> 3000K	90	1130	2248	
		<b>835</b> 3500K	85	1350	2923	
		<b>840</b> 4000K	85	1385	2972	
	F 52°	<b>827</b> 2700K	85	1155	1451	
		<b>927*</b> 2700K	90	990	1258	
		<b>830</b> 3000K	85	1215	1525	
		<b>930*</b> 3000K	90	1100	1397	
		<b>835</b> 3500K	85	1310	1654	
		<b>840</b> 4000K	85	1355	1731	



## HR3LEDT718P



Example: HR3LEDT718PF835CB

### COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

#### New Construction

<b>HR-3LED-H18D1-ICAC</b> Narrow, IC-Rated, Airtight	120V-277V	<b>HR-3LED-H18D1-ICAC</b> Narrow, IC-Rated, Airtight Chicago Plenum	120V-277V
<b>HR-3LED-H18D-ICAC</b> IC-Rated, Airtight	120V-277V	<b>HR-3LED-H18D-ICAC</b> IC-Rated, Airtight Chicago Plenum	120V-277V
<b>HR-3LED-H18D-EMICA</b> IC-Rated, Airtight Emergency Backup Battery	120V	<b>HR3LED-H18D-EMICAF</b> IC-Rated, Airtight Emergency Backup Battery	277V
<b>HR-3LED-H18D-A</b> New Construction Non-IC, Airtight	120V-277V		

#### Remodel

<b>HR-3LED-R18D-A</b> Non-IC, Airtight	120V-277V	<b>HR-3LED-R22D</b> Non-IC	120V-277V
-------------------------------------------	-----------	-------------------------------	-----------

### REPLACEMENT MODULES

#### Reflectors

Narrow Flood	<b>SL-REF-BL10-1-N</b>
Flood	<b>SL-REF-BL10-1-F</b>

#### LED

2700K (90 CRI)	<b>BXRC-27G1000-B-23</b>
2700K	<b>BXRC-27E1000-B-23</b>
3000K (90 CRI)	<b>BXRC-30G1000-B-23</b>
3000K	<b>BXRC-30E1000-B-23</b>
3500K	<b>BXRC-35E1000-B-23</b>
4000K	<b>BXRC-40E1000-B-23</b>

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760