InvisiLED® Palette

24V RGB Color Changing LED Tape Light



PRODUCT DESCRIPTION

InvisiLED[®] Palette is a color changing tape light that transitions through the entire visible color spectrum for a unique and custom lighting effect. The colors progress in a constant flowing manner with adjustable speed and brightness to adapt to any environment.

FEATURES

- Ultra thin profile at 1/8"
- · Diodes spaced evenly at 1" on center
- DMX controller option (consult factory)
- · Wireless controller available
- Select from any color to visibly change an interior design
- Switch to warm 3500K white light with the push of a button
- Run a program to change the speed and brightness
- Minimum run length of 1' and maximum of 40'
- May be field cut every 6" at the end of a run
- Three mounting methods provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

WAC LIGHTING

Responsible Lighting®

Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

SPECIFICATIONS

Construction:	Flexible, silicone cased tape light. Peel and stick 3M
	construction adhesive on back.
	Indicating marks on back for field cutting.
Power Supply:	Remote and plug-in electronic Class 2 transformers.
	120VAC 50/60Hz input, 24V 60W output.
Light Source:	12 LEDs per foot
Dimming:	May be dimmed with WAC wired (LED-TC-CTR-MSD)
	/ wireless controller (LED-TO24-WS)
Operating Temp:	-4°F – 122°F (-20°C – 50°C), relative humidity 95%.
Standards:	UL & CUL Listed for damp locations.

ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Length	Light Color			
LED-TC	1.5	1 1-40 5	1 foot 1 foot (qty 40) 5 feet	RGB	Color Changing	

LED-TC-___-RGB

Example: LED-TC-5-RGB

-	— 1' and 5'	sections		ŧ
0000	φ	φ	$\overline{}$	3⁄8"
	- 1	"		ł

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2016

InvisiLED® Palette 24V RGB Color Changing LED Tape Light

WAC LIGHTING

Responsible Lighting®

Class 2 Power Supply (Require Type	ea) Model	In	put	Output	Max Run	Dim		
			·					
Remote	EN-2460D-C	12	OVAC	24VDC/60W	40 feet	Yes	Includes d	16 foot lead wire
Plug-in	EN-2460D-C-P	12	OVAC	24VDC/60W	40 feet	Yes	Includes d	a 6 foot lead wire
Controller								
Controller (required)		LED-TC-CTR-MSI	D 5 feet	Switch from color changing to white light Play/Pause the color changing effect Control the brightness and speed of the color changing effect Switch for master, slave and DMX functions A controller is needed for every 40 feet run			nanging effect	
Wireless Controller(optional)	CD P CLA	LED-TO24-WS	5 feet	<i>Use to switc Play/Pause</i> Control the	Wireless connection to Master Controller. Use to switch from color changing to white light Play/Pause the color changing effect Control the brightness and speed of the color changing effect Uses 2 AAA batteries.			
Signal Wire	\sim	LED-TC24-SW60 LED-TC24-SW120	5 feet 0 10 feet		ance between i ory for DMX co			d Slave Controller
Accessories	~							
Aluminum Channel		LED-T-CH	5 feet	Includes a d	iffuser, two end	l caps, an	d five screw	'5
Deep Aluminum Channel		LED-T-CH1	5 feet	Includes a d	iffuser, two end	l caps, an	d five screw	'5
45° Angled Aluminum Channel		LED-T-CH2	5 feet	Includes a d	iffuser, two end	l caps, an	d five screw	'5
Fixed Angle Channel Clip	et le	LED-T-CL3-PT	5 feet		ınt any alumin ieces, 4 screws	um chan	nel	
Adjustable Channel Clip	Con .	LED-T-CL2-PT	5 feet	Adjusts 50°	ınt any alumin from center eith ieces, 4 screws		nel	
Retrofit Channel		LED-T-RC	3 feet	Creates fixed	d curves			
Clip	1	LED-T-CL	10 pcs		pe from the un pieces, 10 screv			
Curve Clip	C	LED-T-CL1	10 pcs		ne tape to secur ieces, 4 screws	e the ang	led tape	
	24-SW60 5 feet 24-SW120 10 feet	Extends distance Master Controller Controller Consult factory fo controller options	and Slave	Joiner Cab	e)-TC-IC2)-TC-IC6)-TC-IC12)-TC-IC36)-TC-IC72	2 in 6 in Connects 12 in tape sections 72 in
-	L: 1½ in			3-Way "Y" Connector	\mathbf{Y}	LEI	D-TC-Y	Connects tape sections
Low Voltage Wiring Box		Neatly houses up to	o two wires	4-Way "X" Connector	-	- LEI	О-ТС-Х	Connects tape sections
Wiring Box	L: 6¼ in	Use when spanning		"L" Connec	tor	LEI	D-TC-L	Connects tape sections
With Switch TB-S	W:15⁄8 in H: 1¼ in	gap in a system layo leaving exposed win		End cap		EE	D-TC-EC	1 cut end cap 1 male end cap

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2016