SOLORAIL™ - model: LM-EN12-150E

WAC LIGHTING

Surface Mount Transformers

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Surface mount electronic low voltage transformer for the WAC Solorail™ system. The canopy style enclosure includes the transformer and the track power feed adapter. The standoff height can be increased by the use of two LM-R extension rods.

FEATURES

- 5" Canopy
- Use with 41/2" (LM-X4) standoff
- · Voltage Drop at Run length 20'
- Dims with electronic low voltage dimmers.
- Built-in auto reset, soft start, short and overload circuit protection features.
- Soft start delayed start feature extends lamp life by limiting abrupt in-rush current to the lamp.
- The surface mount canopy transformer is an ideal choice when the installation is on an existing ceiling.
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Power: Input - 120V (60Hz), Output - 12V 150W maximum load, 20W minimum only

Mounting: Installs to a standard junction box. Total weight = 2.3 lbs. The standard LM-EN12-150E configuration matches the height of the $4\frac{1}{2}$ " standoffs.

Finishes: Available in Dark Bronze (DB) and Brushed Nickel (BN).

Standards: UL & CUL listed

ORDER NUMBER

Model	Power	Finis	sh
LM-EN12-150E	150W	BN	Brushed Nickel

LM-EN12-150E	-	

Example: LM-EN12-150E-BN

EXTENSION RODS

Model	Length		Finish		
LM-R	12 24 36	12" 24"	BN	Brushed Nickel	
	36 48	36" 48"			