
SOLORAIL™ - model: LM-EN12-250E

WAC LIGHTING

Surface Mount Transformers

Responsible Lighting®





| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location: | |

PRODUCT DESCRIPTION

Surface mount electronic low voltage transformer for the WAC Solorail™ system. The canopy style enclosure includes the transformer and the track power feed adapter. The standoff height can be increased by the use of two LM-R extension rods.

FEATURES

- 6" Canopy
- Use with 41/2" (LM-X4) standoff
- · Voltage Drop at Run length 16'
- Dims with electronic low voltage dimmers.
- Built-in auto reset, soft start, short and overload circuit protection features.
- Soft start delayed start feature extends lamp life by limiting abrupt in-rush current to the lamp.
- The surface mount canopy transformer is an ideal choice when the installation is on an existing ceiling.
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Power: Input - 120V (60Hz), Output - 12V 250W maximum load, 20W minimum load

Mounting: Installs to a standard junction box. Total weight = 2.5 lbs. The standard LM-EN12 configuration matches the height of the $4\frac{1}{2}$ " standoffs.

Finishes: Available in Dark Bronze (DB) and Brushed Nickel (BN).

Standards: UL & CUL listed

ORDER NUMBER

| Model | Power | Finis | sh |
|--------------|-------|-------|----------------|
| LM-EN12-250E | 250W | BN | Brushed Nickel |

LM-EN12-250E -

Example: LM-EN12-250E-BN

EXTENSION RODS

| Length | | Finish | | |
|----------------------|--------------------------|----------------------------|----------------------------------|--|
| 12 24 36 48 | 12" 24" 36" 48" | BN | Brushed Nickel | |
| | | 12 12" 24 24" 36 36" | 12" 24 24" 86 36" BN | |