


EXTERMINATOR II - model: MO-1035

Monopoint Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Museum-quality LED luminaire with high performance optics

FEATURES

- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Ceiling and wall mountable
- 60,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum with removable front cap for easy change of lenses or accessories

Power Consumption: 35W

Input: 120V-277V AC 50/60HZ

Dimming: Electronic low voltage (ELV) dimmer 100%-5% (120V only)
0-10V 100% - 5% (120V - 277V)

Finish: Powder coated

Standards: UL & cUL Damp Location listed, Energy Star 2.0, Title 24 JA8-2016 Compliant.

ORDER NUMBER

Model	Beam	Color Temp	CRI	Lumens	CBCP	Finish	
MO-1035	N 25°	827	2700K	85	2487	8723	BN <i>Brushed Nickel</i> BK <i>Black</i> WT <i>White</i>
		927	2700K	90	2020	7069	
		830	3000K	85	2652	9279	
		930	3000K	90	2176	7517	
		835	3500K	85	2773	9710	
	840	4000K	85	2795	9748		
	F 55°	827	2700K	85	2476	3409	BN <i>Brushed Nickel</i> BK <i>Black</i> WT <i>White</i>
		927	2700K	90	2029	2824	
		830	3000K	85	2691	3700	
		930	3000K	90	2185	3035	
835		3500K	85	2815	3873		
840	4000K	85	2828	3886			

MO-1035 - _____ - _____

Example: **MO-1035N-927-WT**

Accommodates one lens accessory and one glare control accessory

LENS ACCESSORIES

Amber	LENS-20-AMB
Blue	LENS-20-BLU
Green	LENS-20-GRN
Red	LENS-20-RED
Frosted	LENS-20-FR
Spread	LENS-20-SPR
Beam Elongating	LENS-20-BEL

GLARE CONTROL ACCESSORIES

Cross Louver	LENS-20P-CRL	BN BK WT
Snoot	LENS-20-SNOOT	

REFLECTORS

25°	SL-REF-BL18-N
55°	SL-REF-BL18-F

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585