## MT-216MH

### 2 Light ES16 Metal Halide Multiple Spot

# WAC LIGHTING

Responsible Lighting®

		Fixture Type:
		Catalog Number:
10"×6"		Project:
	18"	Location:
100 100		

10%" × 5%"

#### **PRODUCT DESCRIPTION**

Rectangle two light gimbal ring style adjustable recessed fixture, available with trim or Invisible Trim™, designed to sit flush with the ceiling for a clean, architectural look. Housing and trim ordered separately.

#### FEATURES

- Integrates high output, excellent light quality and superb energy efficiency in a compact package equal in size to an MR16 halogen
- Provides improved discharge arc offering excellent color stability and color rendering
- Best choice for retail applications where there is minimal on/off operation
- Trim version has a ¼" low profile, Invisible Trim<sup>™</sup> sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 25° vertical adjustment and 350° horizontal rotation
- 20W or 39W lamping
- 5 year WAC Lighting product warranty

#### **TRIM ORDER NUMBER** FINISHES WT/BK WT/WT Model # Finish - Trim/Interior White/Black MT-216 WT/BK WT/WT White/White MT-216 Example: MT-216-WT/WT INVISIBLE TRIM™ ORDER NUMBER FINISH wт MT-216TL-WT WAC Lighting

www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. MAY 2012

#### SPECIFICATIONS

**Construction:** Stamped metal trim and aluminum housing. Frame, junction box and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch and chain wiring.

**Ballast:** Pulse start electronic ballast, 120V/277AC input. Thermal protection provided to prevent against overheating and misuse of insulation near fixture.

Light Source: Utilizes two 20W or 39W ES16 metal halide lamps with GX10 base. Lamps sold separately.

**Mounting:** Supplied with hanger bars, adjustable from 15"-24½" to accommodate various joist construction and grid sizes. Accommodates surface of ½" to 1" thick. 5%" × 9%" cutout with trim, 5%" × 9%" cutout for Invisible Trim<sup>™</sup>.

Finish: Trim version – White Trim/Black Interior (WT/BK) and White Trim/White Interior (WT/WT). Invisible Trim<sup>™</sup> – White interior only.

Rating: Non-IC: Insulation must be kept at least 3" away from housing.

Standards: UL & CUL Listed. Suitable for damp locations.

#### HOUSING ORDER NUMBER

Model #	Watt		
MT-216MH	20	20W	
	35	39W	

MT-216MH	-	

Example: MT-216MH-35