Loophole Pendant PD-23852



PRODUCT DESCRIPTION

Clever design details like weighted fasteners that keep the pendant level and coated suspension wires that deliver power take this luminaire to the next level, while the elegant center loop projects in 360-degrees for ambient and task light.

FEATURES

- · Flexible composite diffuser
- Thin powered cables provide an ultra-clean look
- Suspension height can be adjusted easily with quick release
- Fasteners maintain tension to hold fixture level
- Can be mounted on a sloped ceiling
- Universal voltage driver (120V-220V-277V) concealed within canopy

Color Temp: 3000k CRI: 90

SPECIFICATIONS

CRI: 90 Dimming: 100% - 5% ELV Rated Life: 50,000 hrs* Input: 120-277V Construction: Aluminum with composite diffuser Finish: Brushed Black, Brushed Aluminum Standards: ETL & cETL listed, Damp listed, Title 24

ORDER NUMBER

Model		Wattage	Voltage	LED Lumens	Delivered Lumens	Finish		
PD-23852	52″	42W	120V-277V	4261	2733	AL BK	Brushed Aluminum Brushed Black	

Example: PD-23852-BK


dweLED.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

Fixture Type:

Catalog Number:

Project:

Location:



WAC LIGHTING retains the right to modify the design of our products at any time as part of the company's continuous improvement program. Feb 2018

Pendant