CHARMED - LED Pendant

PD-54901



| nber: |
|-------|
| |
| |
| |
| |

PRODUCT DESCRIPTION

Off the chain brilliance, alone or in pairs.

FEATURES

- Thin powered aircraft cables provide an ultra-clean look
- 2.76" x 1.26" x 1.18" universal driver (120V 220V 277V)
- · Can be mounted on a sloped ceiling
- Color Temperature: 3000K
- CRI: 90
- Rated Life: 54,000 hours
- Title 24 option available for special order (driver within canopy)

SPECIFICATIONS

Construction: Aluminum with compose diffuser

Input: 120V - 277V


Dimming: 100% - 10% ELV

100% - 10% ELV; 100 % - 5% 0-10V/Triac (T24 Option)


Light Source: High output LED

Finish: Soft Gold (SG), Brushed Nickel (BN)

Standards: ETL & cETL Damp Location listed



Canopy dimensions:



ORDER NUMBER

| OND EN TROMBER | | | | | | | |
|----------------|------|------|------------|------------------|-----------------------------------|--|--|
| Model | Size | Watt | LED Lumens | Delivered Lumens | Finish | | |
| PD-54901 | 4" | 15W | 1100 | 757 | SG Soft Gold BN Brushed Nickel | | |

Example: PD-54901-SG

For Title 24 option, add "T24" beofre the finish: PD-54901-T24-SG

dweLED.comPhone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760