MULTIPOINT – model: QMP-G3RE

Quick Connect[™] Canopy

WAC LIGHTING Responsible Lighting®

	Fixture Type:
	Catalog Number:
	Project:
	Location:
	© © © 4½″
	26"

PRODUCT DESCRIPTION

Quick Connect[™] multipoint canopy for use with low voltage Quick Connect[™] QP series pendants and QF series track heads. Designed to be installed on ceilings or wood surfaces.

FEATURES	SPECIFICATIONS
 3 x 1W minimum load required 3 x 60W Integral electronic transformers Smooth and continuous ELV dimming 	 Power: Contains 60W integral 12V electronic transformers (3) Electronic transformers have advanced auto-reset, soft start and short circuit protection features. The soft start delayed lamp start feature extends lamp life by delaying the abrupt inrush current to the lamp. Standards: UL & CUL listed Mounting: Mounts over a standard 4" junction box. Base plate covers junction box opening, the canopy attaches to base plate with three screws. There are two trade sized knockout on the base plate. Materials: Etched glass fascia plate as a decorate element. Back plate is galvanized steel. Three transformers (model EN-1260-R-AR) are electronic low voltage, pre-wired into three quick connect adaptors. Mounting hardware, including screws and wire nuts.
ORDER NUMBER	
Model # Finish QMP-G3RE MR Mirror	
QMP-G3RE – MR	

Example: QMP-G3RE-MR

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. MAY 2016