


R-432

4" Line Voltage Downlight Trim



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Recessed trim gimbal ring - 20° adjustment from vertical.
For use with R-400 series Line voltage downlight housings.

FEATURES

- Durable stamped metal construction
- Retention clips hold trim firmly to housing
- Abrasion resistant powder coat paint or plated metal finish
- Handles surfaces up to 3/4"
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable stamped metal construction.
Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Utilizes LED PAR20 lamp or medium base incandescent.
Incandescent lamps are rated for up to 50W watts max. Compact Fluorescent lamps are rated for 13 watts max. Lamps are ordered separately.

Finish: Abrasion resistant powder coat painted or plated metal finish. Trim is available in Brushed Nickel (BN), Copper Bronze (CB) or White (WT).

Standards: UL & CUL Listed. Suitable for damp locations.

ORDER NUMBER

Model Finish

R-432	BN	Brushed Nickel
	CB	Copper Bronze
	WT	White

R-432 -

Example: **R-432-CB**

FINISHES



LED PAR20 LAMP (ORDER SEPARATELY)

PAR20LED-10N30	BK	Black
	WT	White

4" Line Voltage Housings (Required)

	Model	Installation	Rating	Voltage
<p><i>IC-Rated New Construction</i></p>	R-4025-N-ICA	<i>New Construction</i>	<i>IC – Airtight Ready</i>	120V
<p><i>Non-IC New Construction</i></p>	R-4005-N-A	<i>New Construction</i>	<i>Non-IC – Airtight Ready</i>	
<p><i>Non-IC Remodel</i></p>	R-4015-R-A	<i>Remodel</i>	<i>Non-IC – Airtight Ready</i>	

Non-IC housings require 3" of clearance from insulation on all sides.
Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting

www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585