

3.5" OCULUX ARCHITECTURAL

Adjustable Pinhole - R3CSPT, R3CSPL

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Oculux Architectural offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angle options included:
Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast aluminum trim and heat sink

Dimming: 100% - 1% TRIAC, ELV
100% - 5%, 0-10V

Input Power: 13.5W, 120V-277V 50/60Hz

Light Source: High output COB LED rated life of 50,000 hours.

Mounting: Retention clips firmly hold trim to housing. Cutout 4¼" x 4¼"





Finish: Powder coated white.

Ceiling thickness: ½" - 1"

Standards: UL & cUL, Wet location listed. Energy Star® 2.0
Title 24 JA8-2016 Compliant

Operating Temperature: -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)

Model	Beam	Color Temp	Lumens	CBCP	Finish
R3CSPL Square Trim Adjustable Pinhole 	Spot 16°	927 2700K	755	5004	WT White 
		930 3000K	810	5380	
		935 3500K	825	5488	
		940 4000K	865	5757	
	Narrow Flood 32°	927 2700K	705	1373	
		930 3000K	760	1477	
		935 3500K	775	1506	
	Flood 44°	927 2700K	645	791	
		930 3000K	695	851	
935 3500K		705	868		
R3CSPT Square Trimless Adjustable Pinhole 	Spot 16°	927 2700K	755	5004	WT White 
		930 3000K	810	5380	
		935 3500K	825	5488	
		940 4000K	865	5757	
	Narrow Flood 32°	927 2700K	705	1373	
		930 3000K	760	1477	
		935 3500K	775	1506	
	Flood 44°	927 2700K	645	791	
		930 3000K	695	851	
935 3500K		705	868		
940 4000K	740	911			

R3CSP__ - _____

Example: R3CSPT-WT

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

3.5" OCULUX ARCHITECTURAL


Adjustable Pinhole - R3CSPT, R3CSPL

WAC LIGHTING

Responsible Lighting®

Housings (Required) - Order separately from trims

Model Color Temp Input



Model	Color Temp	Input
R3CSN-11	927 2700K	120V - 277V
<i>IC-Rated, Airtight</i>	930 3000K	
<i>New Construction</i>	935 3500K	
	940 4000K	

Example: **R3CSN-11-927**

GLARE CONTROL ACCESSORIES sold separately

LENS-16	HCL	Honeycomb Louver

FEATURES

- Adjustable LED light engine included with housing:
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

LENS ACCESSORIES sold separately

LENS-16	AMB	Red
	RED	Frosted
	SPR	Spread
	BEL	Beam Elongating

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760