

LOTOS 4" & 6" LED Recessed R4ERDR/R6ERDR

WAC LIGHTING Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Shallow profile LED that is designed to fit in furred down ceilings without sacrificing lumen output. Available in 4" or 6" recessed or 4" adjustable LED recessed.

FEATURES

- Heavy gauge retention clips secures fixture to ceiling
- Installs into ceilings between ½" and 1½" thick
- Height: Fixture - 1", Driver 1¼"
- 50,000 hour rated life
- 5 year warranty
- 90 CRI

SPECIFICATIONS

Construction: Steel with translucent diffuser

Input: 120 -277V

Dimming: 100% - 10% ELV, 100% - 5% TRIAC

Harmonic Distortion (THD): <20%

Operating Temperature: -20°C (-4°F) to 40°C (104°F)

Standards: Title 24 JA8-2016 Compliant; Energy Star® rated; Wet location listed; ETL listed

ORDERING NUMBER

	Model	Power	Beam	Max Lumens	Color Temp	Finish
	R4ERDR 4" Round Downlight IC - Rated, Airtight Wet Location Listed	9W	W	550	930 3000K	WT White
	R6ERDR 6" Round Downlight IC - Rated, Airtight Wet Location Listed	14W	W	1000	930 3000K	WT White

R ERDR-W930 - WT

Example: R4ERDR-W930-WT

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760