


44 Harbor Park Drive Port Washington, NY 11050 Tel: 800.526.2588 www.waclighting.com

5" PREMIUM DOWNLIGHT TRIM

R5VT-24





Ordering Matrix							
Series	Model Number	Finish					
R5VT	24	ВК	WT				

Ordering Example (series - model number - finish): R5VT-24-BK

Product Details

Application: Ceiling down light trim, 1-inch maximum ceiling thickness.

Provides smooth broad area illumination without shadows. Used with incandescent or fluorescent lamp housings.

Materials: One-piece spun aluminum construction. Integral trim ring is

painted white, interior reflector is anodized aluminum. Trim is

retained to socket via spring clips.

Finish: BK = Black with White trim

WT = White with White trim

Ratings: UL & CUL listed.

Specification Features

- · Suitable for damp locations
- 5 year WAC Lighting product warranty.

Compatible Housing R5VI-ICA Insulation Contact & Air Tight New Construction Incandescent Lamp: PAR30 50W	s (sold separately)	R5VI-R-ICA Insulation Contact & Air Tight Remodeling Incandescent Lamp: PAR30 50W	R5VI Non IC Frame-in Style New Construction Incandescent Lamp: A19 75W PAR30L 75W	
R5VI-S-ICA Insulation Contact & Air Tight Shallow New Construction Incandescent Lamp: PAR30 50W		R5VI-S-R-ICA Insulation Contact & Air Tight Shallow Remodeling Incandescent Lamp: PAR30 50W	R5VF-113Q Non IC Frame-in Style New Construction Fluorescent Lamp: Quad 13W G24Q-1	



44 Harbor Park Drive Port Washington, NY 11050 Tel: 800.526.2588 www.waclighting.com


5" PREMIUM DOWNLIGHT TRIM

R5VT-24

R5VF-126/32T

Non IC Frame-in Style New Construction Incandescent Lamp: Tri-tube 26/32W GX24Q-3





Socket cup adds a maximum of 2 1/8" to the height of the trim when used with frame in kits.