
LOUVER BRICK LIGHTS Endurance[™]

WL-5205





WAC LIGHTING

Responsible Lighting®

Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

PRODUCT DESCRIPTION

Die cast aluminum factory sealed housings with patent pending design for a water and dust proofing. IP66 rated outdoor brick light

FEATURES

- IP66 and ETL & cETL Wet Location Listed
- ADA Compliant
- Factory-Sealed LED Light Engine
- Die-Cast Aluminum Construction (K-Alloy)
- 120V Direct Wire No Driver Needed
- Glare controlling die casted aluminum louver.

SPECIFICATIONS

Construction: Die-cast aluminum (K-Alloy) Power: Line Voltage input (120V), 50/60Hz **CRI:** 90 Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer Finish: Architectural Bronze, Black, Graphite and White Standards: IP66, ADA, ETL & cETL Wet Location Listed Rated Life: 80,000 hours Operating Temperature: -40°C to 50°C (-40°F to 122°F)

ORDER NUMBER

		Power	Max Delivered Lumens	Color Temp	Finish		
WL-5205-30	Louver	5.5W	45	3000K	ABZ ABK AGH AWT	Architectural Bronze Architectural Black Architectural Graphite Architectural White	

Example: WL-5205-30-AWT

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 2017