



Fixture Type:	
Catalog Number:	
Project:	
location:	

SPECIFICATIONS

Construction: Aluminum body with acrylic diffuser

Input: 120V-277V Dimming: 100% - 10% ELV

Light Source: High output LED

Finish: Brushed Nickel (BN), Chrome (CH)

Standards: ETL/cETL, Damp location listed, ADA Compliant


FEATURES

- Etched acrylic diffuser
- LED modules positioned closer to diffuser for broader spread of illumination
- 2.76" x 1.26" x 1.18" universal voltage driver (120V-220V-277V) installs within a junction box
- Color Temperature: 3000K
- CRI: 90
- Rated Life: 50,000 hours

Replacement Driver

RPL-DRV-70016	
RPL-DRV-70028	

Driver Driver





ORDER NUMBER

Model	Size	Watt	LED Lumens	Delivered Lumens	Finis	sh	
WS-69815 15"	15"	10W 84	845	636			
WS-69826	26"	20W	1784	1240	BN CH	brushed Nickel Chrome	
WS-69838	38"	30W	2712	2136	СП		

Example: WS-54919-BN

dweLED.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

dweLED retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEb 2019